

Polypropylene Fiber for Concrete Application.

DEFINITION

Novo Concrete Fiber is new generation alkaline resistance chopped strand fiber produced from polypropylene. This reinforcing fiber is especially used to prevent plastic shrinkage.

Novo Concrete Fiber is chemically inert for all type Portland cement mixes and to the weather conditions, so it will not lose its strength and impact resistance over time.

USES

Novo Concrete Fiber user with all type of concrete mortar and construction with formed part to increase its impact resistance and prevent plastic shrinkage, use as reinforcing sharp plaster corners and edges, epoxy mortar.

ADVANTAGES

1. Inert for all alkaline
2. Inert for solvent and epoxy resin
3. Low thermal conductivity
4. Anti-bacteria.
5. Light weight and high strength

PHYSICAL PROPERTIES @ 25 C°

DISCRIPTION	VALUE
<i>Color</i>	White (100% propylene)
<i>diameter</i>	(17 micron
<i>Length</i>	6, 12 ,18 mm
<i>Surface area</i>	≥ 225 m ² /kg
<i>Shelf life</i>	24 months in suitable conditions



DIRECTION OF USE

1. Added directly to concrete mortar and mixed well where should be good homogeneous distributed in mortar of concrete or epoxy mortar.

Dosage:

To reinforced concrete layer:

- 0.9 kg of **Novo Concrete Fiber** per m³ of concrete mix

To reinforced plaster and layer or mortar

- 0.5 kg of **Novo Concrete Fiber** per 50 kg of cement
- To reinforced epoxy mortar and paints
- 5- 10 % of epoxy resin by weight

STORAGE CONDITIONS

- Best stored at room temperature in dry conditions. (10-30) C°
- Avoid humidity, cold freezing conditions and off concrete floors.
- Do not store in direct sunlight.

PACKING

- Plastic Sack 0.9 kg

PRECAUTIONS & SAFETY

- **Novo Concrete Fiber** is non - flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.

NOVOCHEM S.AE

المقر الرئيس والمصنع

مصر - الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

 www.novochem.net

 info@novochem.net

  Novochem

