

Good quality Ceramic Adhesive.

DEFINITION

Novo Tile 140 is a cementation based on powder and available in grey or white color.

Novo Tile 140 is contained selective raw materials that resist the growth of bacteria and mold on the surface.

USES

Novo Tile 140 is a good quality adhesive for tiles, ceramic and hard foam panel, etc.

ADVANTAGES

1. Ready to use (only mixing with water)
2. Good open time
3. Good slip resistance.
4. Anti-bacteria.
5. High adhesive and bond strength.

PHYSICAL PROPERTIES @ 25 C°

DISCRIPTION	VALUE
<i>Color</i>	White, gray
<i>Coverage</i>	3- 4 kg / m ² (depending on surface conditions)
<i>Shelf life</i>	12 months (under suitable storage conditions)



DIRECTION OF USE

1. The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.
2. Moisture the surface and ceramic by water before application with 10 minutes.
3. Add (4 – 5) liter/ 25 kg - of water clean pail then add (powder) step by step with continuous stirring by suitable mixer (small quantity can be mixed by hand). mixing well until obtain good homogenous putty without any lumps
4. Let mixed putty for 5 minutes the mix again for 3 – 5 minutes to be ready for application
5. Applied the ready product on the surface by a comb knife or by suitable tools
6. Place tiles firmly into the adhesive bed ensuring good contract with a twisting motion. Only apply to areas which can be tiled in the adhesives' open wet time (Approximately 30 min. @ 25 C°).
7. Remove excess products from sides and joints by wet clothes or wet cotton.
8. Clean used tools by water immediately after finish

STORAGE CONDITIONS

- Best stored at room temperature in dry conditions. (10 – 30) C°
- Avoid humidity, cold freezing conditions and off concrete floors.
- Do not store in direct sunlight.

PACKING

- Plastic Sack 25 kg

PRECAUTIONS & SAFETY

- **Novo Tile 140** is non - flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.

NOVOCHEM S.AE

المقر الرئيس والمصنع

91.102.103 الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

www.novochem.net

info@novochem.net

[Novochem](#)

