

## Exterior & Interior high quality plastic Semi-gloss paint.

### DEFINITION

**Novo Dolux** is high quality Semi-gloss emulsion paint based on special high quality acrylic polymer, Titanium dioxide and special fillers which are a Semi-gloss finish coat for interior and exterior use.

### ADVANTAGES

1. Easy apply.
2. High abrasion resistance.
3. Washable emulsion paint.
4. Adheres well and can be applied on all surfaces of building.
5. White and colored to suit all tastes.

### FIELDS OF USE

1. Use for cement, plastered walls, ceilings, concrete work, gypsum board partitions and internal gypsum roof etc.
2. Suitable For homes, schools, hospitals, office buildings, hotels ...etc.

### PHYSICAL PROPERTIES @ 25 C°

DISCRIPTION	VALUE
<i>Color</i>	White and colored
<i>Glossy</i>	Semi-gloss
<i>Density</i>	(1.30 ±0.05) kg / L
<i>Viscosity</i>	20-30 poise
<i>PH</i>	8- 9
<i>Coverage</i>	8– 10 m <sup>2</sup> /kg (depending on surface conditions)
<i>Shelf life</i>	12 months (under suitable storage conditions)

#### NOVOCHEM S.AE

المقر الرئيس والمصنع

مصر – الجيزة – مدينة السادس من أكتوبر – المنطقة الصناعية الثالثة – بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6<sup>th</sup> of October City - 3<sup>rd</sup> Industrial Zone - Blocks 91,102,103

### SURFACE PREPARATION

1. The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.
2. The surface should be sealed by **Novo Latex Sealer** if required.
3. Apply one or more coat Novo putty to smoothing the surface.
4. Cavities can be filled with **Novo Putty**.
5. Apply one coat of novo undercoat emulsion paint.

### DIRECTIONS OF USE

#### Mixing before use

**Novo Dolux** should be mixed well before using to obtain homogenous liquid.

#### Applications

- Apply one or more coats of **Novo Dolux** by suitable roller, brush or by spray.

**Novo Dolux** can be diluted with clean water 1 -5 % if required to facilitate the application.

#### Guide coating system for Interior and Exterior

Primer Sealer	Novo Latex Sealer	1 Coat
Putty	Novo Putty	2 Coats
Under Coat	Novo Eco	1 Coat
Finish Coat	<b>Novo Dolux</b>	1-2 Coat

### STORAGE CONDITIONS

- Best stored at room temperature in dry conditions.
- Avoid humidity, cold freezing conditions and off concrete floors.
- Do not store in direct sunlight. (10-30) C°

### PACKING

- Plastic Pail 15 lit
- Gallon 4 lit (As customer require)

### PRECAUTIONS & SAFETY

- **Novo Dolux** is non - flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

[www.novochem.net](http://www.novochem.net)

[info@novochem.net](mailto:info@novochem.net)

[Novochem](#)

