

Ready to use Interior wall putty. complies to Egyptian Standard Specification No. 623\2008.

DEFINITION

Novo Go Putty is ready use emulsion putty based on acrylic co-polymer emulsion especially selected powders, fillers, additives.

Novo Go Putty complies to Egyptian Standard Specification No. 623\2008.

ADVANTAGES

1. Ready to use and easy to apply with its enhanced properties
2. give a smooth finish to walls
3. it is easily sanded to give the perfect finish required with high quality tabs
4. Can be used as an under layer for all types of paints and wall papers.

FIELDS OF USE

1. Ready to use for smoothing cement or lime based on plasters, paper or whenever a super smooth surface is required.
2. Also, concrete walls before applying of all types of paints.
3. Also be used for filling small holes producing any cracks.

PHYSICAL PROPERTIES @ 25 C°

DISCRIPTION	VALUE
<i>Color</i>	White
<i>Glossy</i>	Matt
<i>Density</i>	(1.75 ±0.05) kg / L
<i>PH</i>	8- 9
<i>Coverage</i>	2 – 3 m ² / kg (depending on surface conditions)
<i>Shelf life</i>	12 months (under suitable storage conditions)

SURFACE PREPARATION

1. The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.
2. The surface should be sealed by **Novo Sealer** if required.
3. Applied by putty knife, only one coat is sufficient for a smooth surface, but a rough surface two or coats are required.
4. Each coat must be dried and sanded down with sand paper before applying a further coat.

Guide coating system for Interior

Primer Sealer	Novo Sealer	1 Coat
Putty	Novo Go Putty	2 Coats

STORAGE CONDITIONS

- Best stored at room temperature in dry conditions.
- Avoid humidity, cold freezing conditions and off concrete floors.
- Do not store in direct sunlight.

PACKING

- Plastic pail & Bag 5 Kg & 15 Kg

PRECAUTIONS & SAFETY

- **Novo Go Putty** is non - flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.

NOVOCHEM S.AE

المقر الرئيس والمصنع


مصر - الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

 www.novochem.net

 info@novochem.net

  Novochem

