

A powder release agent for printed concrete.

DEFINITION

Novo Color Release a chemicals powder used as a release agent for use a printed concrete to easy remove mould and to achieve a clean release.

USES

It is designed to be used on printed concrete floors to easily remove stamps and to achieve a clean release.

ADVANTAGES

1. Better release properties.
2. Non-staining.
3. Does not affect cement hydration.

PHYSICAL PROPERTIES @ 25 C°

Color	As color hardener
<i>Specific Gravity</i>	2
<i>Chloride content</i>	Nil
<i>Theoretical Coverage</i>	6 – 8 m ² / Kg

DIRECTION OF USE

Application:

- Upon completing final troweling of integral colored or color hardened concrete, apply a light even coat of Concrete Release Agent over the area to be imprinted.
- Allow bleed Water to dissipate before broadcasting Release Agent on surface.
- Release Agent shall be applied in one or more broadcasts.

Use “hand” or dry calcimine brush broadcast method, applying evenly and consistently. It is generally recommended that the Release Agent is a complimentary contrasting color, usually darker than the concrete. Do not add water to surface while imprinting over Release Agent.

STORAGE CONDITIONS

- One year in its original packs stored at favorable conditions transport.
- Do not store in direct sunlight.

PACKING

- Packs 15 kg

PRECAUTIONS & SAFETY

- **Novo Color Release** is non-toxic. Any splashes to the skin should be washed immediately with Water.
- Splashes to the eyes should be washed immediately with water and medical advice should be sought.
- Wear a face mask against dust if there is a heavy dust development.
- Do not dispose of into water of soil but according to Local regulations.
- Non - hazardous, no problems during Transport.

ADDITIONAL INFORMATION

- NovoChem Provides the Construction industry with a comprehensive range of construction chemicals and specialty products answering the queries of modern engineers for trouble free durable structure
- NovoChem designs tailor made products. should their critical application that requires specific properties rather than our main range.
- For our customers satisfaction, NovoChem extends technical services to include after sales support to assist users in a proper handling of our products.

NOVOCHEM S.AE

المقر الرئيس والمصنع

91.102.103 الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

 www.novochem.net

 info@novochem.net

  Novochem



NOVOCHEM S.AE

المقر الرئيس والمصنع

مصر - الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

 www.novochem.net

 info@novochem.net

  Novochem

