

Colored Dry shake surface hardener for Stamped concrete.

DEFINITION

Novo Color Top is a ready to use dry. shake color hardener. It is formulated to be easily integrated into the surface of the freshly placed concrete.

Novo Color Top consists of a special grade of very hard-wearing aggregates, cement, additives for high workability and pigment.

Novo Color Top easy to apply to fresh wet concrete by band trowel, mechanicals trowel and stamps forms. Regarding the monolithic property, it is easy to avoid the problems of thin screeds such as, shrinkage curling and etc...

USES

- It is regularly used as a floor hardening and coloring agent with flat work and stamped concrete to stimulate the look of brick stone, tile, slate, etc.
- **Novo Color Top** is also used in institutional, industrial, commercial and residential applications for flat concrete floors where abrasion resistance and colored floor is desired.

ADVANTAGES

- provides hard, durable, abrasion resistance hard capes. it offers streak-free, uniform color in a wide color selection.
- Due to its dense surface, it is longer wearing, easier to maintain, and more resistance to the effects of freeze thaw cycles.
- Special colors according to customer needs

COVERAGE

3 Kg/m² Light duty.

5 Kg/m² Medium duty.

7 Kg/m² heavy duty.

BASE CONCRETE

- The same plant should batch all concrete to avoid variation.
- All concrete should be placed at the same slump.
- Concrete should be placed and screened with normal

Procedures.

- At this point the concrete should be floated with a wood or Magnesium bull floats.

APPLICATION

- After initial floating and all excess bleed water dispersed, broadcast first application Novo Color Top using about 60% of recommended amount and let it remain on the surface for several minutes or until Novo Color Top has wetted out sufficiently, then float with a wood or magnesium float.
- Immediately broadcast the second application with remaining of Novo Color Top and let it went out for several minutes then trowel it.

NON-SKID FINISH

- To achieve a non-skid finish, broadcast second application of Novo Color Top and do not trowel or work into concrete, let it sit for a few minutes or until ready to stamp apply release powder and stamp as usual, this will produce a more textured nonskid surface.
- After the concrete has achieved its setting the release agent may be removed by pressure rinsing with a high-power pressure cleaner, or a soap and water solution and scrubbed with a broom.

SEALER

To protect and help cure the concrete, two coats of Novo Guard Clear sealer are recommended.

HEALTH AND SAFTY

- Wear protective cloths, gloves, glasses and face protection.
- For skin contact, remove it by soap and clean water.
- For eye contact rinse with plenty clean water and then seek medical advice.
- For more details, require safety data sheet for the product.

NOVOCHEM S.AE

المقر الرئيس والمصنع

91.102.103 الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

 www.novochem.net

 info@novochem.net

  Novochem

