

High quality – semi gloss One Component Traffic & road marking

DEFINITION

Novo Route LP64 S2 is ready to apply as a road marking. One component based on selective synthetic acrylic resin, pigment and high selective fillers to give good results to be used for long lasting road marking.

USES

Novo Route LP 64 S2 is used for

- Marking asphalt and concrete flooring of roads.
- High ways, garages, parking and loading areas

ADVANTAGES

Novo Route LP64 S2 is

- Fast drying.
- Highly abrasion resistance.
- Good weather resistant.

PROPERTIES @ 25 C°

DESCRIPTION	RESULT
<i>Color</i>	white, black, yellow, red
<i>Glossy</i>	Semi-gloss
<i>Solid of pigment by wt.</i>	(37±2) %
<i>Total Solid by wt.</i>	(57 ±2) %
<i>Total Solid by vol.</i>	(30 ±2) %
<i>Density</i>	1.40 ± 0.03 gm. /cm ³
<i>Viscosity</i>	90 ± 5 Ku
<i>Surface dry</i>	20 Min
<i>Hard dry</i>	1 hr.
<i>Suggested D.F.T</i>	150 – 300 Micron
<i>Thinner</i>	Novo Sol 13 Or Novo Sol X2
<i>Rate of use</i>	2-3 M ² /kg/100 μ DFT (Depends on surface state)
<i>Shelf life</i>	12 months in suitable storage conditions

DIRECTION FOR USE

- The surface should be free from dust, oil, and loose particles.
- Apply one or more coat from **Novo Route LP 64 S2**, by using brush, roller, or spray
- Use **Novo Sol X 2** or **Novo Sol 13** as thinner and to clean the tools after application. (5-10)%

REFLECTIVE PROPERTIES

- Highly Night Vision
- We deliver the most advanced technology of Glass beads with our road marking coat. Our "Echo Star" grade of glass beads has a unique Crystal-clear glass with very spherical shapes "Echo star" glass beads have properties like:
 - Double coating adherent.
 - Double float adherent.
 - Higher refractive index.

STORAGE

One year under suitable storage conditions. (10 – 25) C°

PRECAUTIONS

- Keep away from sources of agitation.
- No smoking during work.
- Good ventilations in case of spray applying.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.
- For eye contact, rinse with plenty clean water then ask for medical advice.



NOVOCHEM S.AE

المقر الرئيس والمصنع

مصر – الجيزة – مدينة السادس من أكتوبر – المنطقة الصناعية الثالثة – بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

www.novochem.net

info@novochem.net

[Instagram](#) [Facebook](#) Novochem

