

Matt Synthetic enamel paint.

DEFINITION

Novo Go Alkyd matt is matt synthetic enamel paint, based on Alkyd resin, and other selected pigments and fillers.

ADVANTAGES

- Easy to apply.
- High coverage because of the use of finely grounded and high-quality pigments.
- After drying, it produces matt elastic homogenous film that is well adhered to the substrate and resisted abrasion and scratching.

USES

- Can be applied on synthetic primer or undercoat or on both...also.
- On wooden, metallic and plastered surface.
- Can be used as high-quality undercoat before application top coat of glossy alkyd paint like **Novo Go Alkyd Glossy**

PHYSICAL PROPERTIES @ 25 C°

DISCRIPTION	VALUE
<i>Color</i>	white and colored
<i>Density</i>	(1.6 ±0.05) kg / L
<i>Viscosity</i>	38 ± 5 poise
<i>Solid content (by WT.)</i>	(80 ±2) %
<i>Solid content (by Vol.)</i>	(50 ±2) %
<i>Surface dry</i>	1 hr.
<i>Hard dry</i>	24 hr.
<i>Full cure</i>	7 days
<i>Thinner</i>	Sol M 8
<i>Shelf life</i>	12 months in suitable storage conditions

NOVOCHEM S.A.E

المقر الرئيس والمصنع

مصر - الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

SURFACE PREPARATION

- The surface of the substrate should be cleaned from oil, grease, dirt, and loose particles.
- The surface should be smoothed well by suitable putty and blasted to be smooth.
- The substrate should be primed or coated with suitable under coat then left to dry and smoothed down with sand paper.
- Steel surface should be plastered and primed by **Novo Prime R**
- Mix well the contents that will be used.
- One or two coats of **Novo Go alkyd -matt** are recommended to apply.
- Can be applied by brush, roller or spraying gun.
- Can be thinned by **Novo sol M 8** if needed.
- Clean tools by **Novo sol T9** or **Novo sol M 8**

COVERAGE

4- 6 m² / kg / 75-micron coat.

(Depending on the surface condition and type)

STORAGE CONDITIONS

- Best stored at room temperature in dry conditions.
- Avoid humidity, cold freezing conditions and off concrete floors.
- Do not store in direct sunlight. (10 -30) C°

PRECAUTIONS & SAFETY

- Wear protective clothes, gloves, glasses and face protection.
- Application should be carried out in well ventilate place
- For skin contact, remove it with suitable cream followed by soap and water cleaning.
- Don't eat or smoke during use.

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

www.novochem.net

info@novochem.net

[Novochem](#)

