

Novo Prime EPW

Last update: - 24 / 06 / 2021 (2)

Water base Epoxy Primer for Epoxy, PU Flooring & Coating System.

DEFINITION

Novo Prime EPW is a low viscosity transparent water base epoxy primer and sealer, which is selected to give a high quality and superior adhesion and flexibility.

ADVANTAGES

- 1. High coverage.
- 2. Applied on wet concrete surface
- 3. Low viscosity.
- 4. Extended pot life.
- 5. Hard wearing.
- 6. Excellent adhesion.

FIELDS OF USE

Novo Prime EPW is used as

- 1. Prime for epoxy flooring coating.
- 2. Dust Proof floor coating in warehouses and industrial areas.

3. Sealer for porous concrete surface.

PROPERTIES @ 25 C°

Color	Transparent
Gloss	Semi-Gloss
Solid content by (WT)	(37±2) %
Mixing Ratio	1 A: 3 B
Specific gravity (mix)	0.98 ± 0.03
Pot life	1 hr.
Temp. of Application	(5 — 35) C°
Full curing time	7 days
Rate of use	7- 10 m ² / kg
Shelf life	12 months in suitable
	storage conditions

DIRECTIONS OF USE

Concrete surface preparation

- The substrate must be clean, sound and free from all contaminants that may affect the adhesion strength like dust, oils and grease, cement laitance, and any contaminants must be removed by blasting or suitable release agent.
- Holes should be filled with **Novo putty EP**.
- Any excessed laitance or dust should be removed before applying novo prime.

Mixing and application

- Add comp A (ensure all liquid of comp A is added) to comp $\mathbf{\underline{B}}$ and mix well manually or by using very slow mixer.
- Application method:
- Novo Prime EPW is applied by brush & roller or spray (Air spray, Airless spray).

STORAGE

One year under suitable storage conditions. Avoid direct sun on storage.

PACKING

- Group 1 & 2.5 & 4 kg
- (As customer require)

HEALTH AND SAFETY

- Wear protective clothes, gloves, glasses and protection.
- Keep away from sources of agitation.
- No smoking during work.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.
- For eye contact, rinse with plenty clean water then ask for medical advice.

NOVOCHEM S.AE

المقر الرئيس والمصنع

مصر — الجيزة — مدينة السادس من أكتوبر — المنطقة الصناعية الثالثة — بلوك 91،102،103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel.: (+202) 369 182 33 Fax: (+202) 369 182 32















