

Cement Grout for Ceramic Tiles.

DEFINITION

Novo Tile Grout is a blend of specially selected cements, fillers and synthetic additives polymers. When added to water, it readily blends to produce a smooth creamy paste which is water and mold resistant.

ADVANTAGES

- Low-cost service life-mold resistant.
- Ensures crack free
- Good adhesion
- Available in a range of attractive colors.

FIELDS Of USE

As a grout for dry tile joints in in all constructions like Flooring tile, Kitchens, Bathrooms, hospital, etc.

PROPERTIES @ 25 C°

Color	White, grey, all required colors
Working time	60 min
Coverage	3- 4 m / kg depend on the type, size and spacing of tiles.
Shelf life	12 months in suitable conditions of storage.

STORAGE CONDITIONS

- Store under suitable storage conditions.
- In dry conditions, in the original unopened bags or packs.
- If stored at a high temperature or high humidity conditions, the shelf life may be affected.

PACKING

Novo Tile Grout: 25 kg bags



DIRECTIONS FOR USE

- All tiles must be securely fixed in place and completely cleaned before **Novo Tile Grout** is applied.
- The gap between tiles should not exceed 4mm.
- The product should not be exposed to moving water during application.
- 4- 5 Liters of water are required for each 25 Kg bag of **Novo Tile Grout** and a slow speed drill fitted with a suitable mixing paddle is recommended.
- Add powder to water and mix until a uniform, lump-free, thick creamy paste is produced, allow stand for ten minutes before use.
- Apply **Novo Tile Grout** to the spaces between the tiles using a sponge or a small piece of soft cloth.
- Pour the mixture into the joints and around the edges.
- Remove surplus material from the face of tiles with a dry cloth and run the tip of a gloved finger or suitable rounded tool along the grout to level it off and form a profile.
- When the grout is dry, clean the tiles with a damp sponge to remove any excess material.

HEALTH AND SAFETY

- **Novo Tile Grout** is non-toxic, non-corrosive and any splashes on the skin should be washed with water.
- If contact with eyes occurs wash well with water immediately and ask for medical advice.



NOVOCHEM S.AE

المقر الرئيس والمصنع

مصر - الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6th of October City - 3rd Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

www.novochem.net

info@novochem.net

[Instagram](#) [Facebook](#) Novochem

