

## Interior & Exterior high quality plastic paint Anti-Bactria.

### DEFINITION

**Novo Super Bio** is high quality anti-bacteria flat emulsion paint based on special acrylic polymer, Titanium di oxide and special fillers which are a flat finish coat for interior and exterior use. It is High resistance to mold, bacteria growth on the dry film surface.

### ADVANTAGES

1. Easy apply.
2. High abrasion resistance.
3. Washable emulsion paint.
4. Adheres well and can be applied on all surfaces of building.
5. Anti-bacterial growth on the dry film surface
6. White and colored suit all tastes.

### FIELDS OF USE

1. Use for on cement, plastered walls, ceilings, concrete work, gypsum board partitions and internal gypsum roof etc.
2. Suitable For homes, schools, hospitals, Office building, hotels etc.
3. Used as undercoat before application top emulsion coat.

### PHYSICAL PROPERTIES @ 25 C°

DISCREPTION	VALUE
<i>Color</i>	White and colored
<i>Glossy</i>	1/4 GLOSSY
<i>Density</i>	(1.30 ±0.05) kg / L
<i>Viscosity</i>	25-40 poise
<i>PH</i>	8- 9
<i>Coverage</i>	3 – 4 m <sup>2</sup> /kg (depending on surface conditions)
<i>Shelf life</i>	12 months (under suitable storage conditions)

### SURFACE PREPARATION

1. The substrate must be sound, clean, dry, free from dust, oil, grease and laitance etc.
2. The surface should be sealed by **Novo GO sealer** if required.
3. Cavities can be filled with **Novo Go putty** or **Novo Pro putty**
4. Apply one coat of under coat **Novo Super Bio**

### DIRECTIONS OF USE

#### Mixing before use

**Novo Super Bio** should be mixed well before using to obtain homogenous liquid.

#### Applications

- Apply one or more coat of **Novo Super Bio** by suitable roller, brush or by spray **Novo Super Bio** can be diluted with clean water 1 -5 % if required to facility the application.

#### Guide coating system for Interior and Exterior

Primer Sealer	Novo Latex Sealer	1 Coat
Putty	Novo Go Putty	2 Coats
Under Coat	Novo Pro	1 Coat
Finish Coat	Novo Super BIO	1-2 Coat

### STORAGE CONDITIONS

It's best stored at room temperature in dry conditions. Avoid humidity, cold freezing conditions and off concrete floors.

Do not store in direct sunlight.

### PACKING

- Plastic Pail 20 Kg & 10 Kg & 5 Kg
- Steel Pail 15 liter

### PRECAUTIONS & SAFETY

- Novo Super Bio** is non - flammable, wash any splashes to the eyes immediately with water, and medical advice should be consulted.
- Wear protective clothes, gloves, glasses and face protection.
- For skin contact, remove it with suitable cream followed by soap and water cleaning.

#### NOVOCHEM S.AE

المقر الرئيس والمصنع

91.102.103 الجيزة - مدينة السادس من أكتوبر - المنطقة الصناعية الثالثة - بلوك 91,102,103

Headquarters and Factory

Egypt - Giza- 6<sup>th</sup> of October City - 3<sup>rd</sup> Industrial Zone - Blocks 91,102,103

Tel. : (+202) 369 182 33

Fax: (+202) 369 182 32

[www.novochem.net](http://www.novochem.net)

[info@novochem.net](mailto:info@novochem.net)

[Novochem](#)

